

# SiLVUS

TECHNOLOGIES

## STREAMCASTER NEXUS™

INTEGRATED TACTICAL COMMUNICATIONS

Empowering The Elite Operator



### Engineered For Mission Mobility

- Available in Juggernaut Armor Mount and Velox Configurations
- Optimized size, weight and power to minimize load-out and maximize operational freedom
- Less than 1.5 lb. and ~1.5 inches thick

### Built for the SM5200

- Up to 2W native / 4W effective output power
- Integrated PTT with Left/Right Audio
- Dedicated ROIP interface
- 1x Ethernet, 2x USB, 1x RS232
- 3-point snap lock system for chest-mounted or standalone radio operation

# STREAMCASTER NEXUS INTEGRATED TACTICAL COMMUNICATIONS

## FEATURES



## SPECIFICATIONS\*

TRANSMIT POWER	NATIVE TX POWER User Adjustable 1mW – 2W	EFFECTIVE TX POWER w/Beamforming Up to 4W
WAVEFORM	Mobile Networked MIMO (MN-MIMO)	
ENCRYPTION	AES256; FIPS 140-3	
DATA RATE	Up to 100 Mbps (adaptive)	
FREQ. BANDS (MHz)	L (1350-1440); S (2200-2500); C (4400-5000)* L8S (1350-1440) + (2200-2500) S&C (2200-2500) + (4400-5000)* <i>*Expected Q4, 2025</i>	
CHANNEL BANDWIDTH (MHz)	20/10/15 (2.5/1.25 Optional)	
SCALABILITY	550+ Nodes	
SPECTRUM DOMINANCE LPI/LPD & ANTI-JAM CAPABILITIES	MANET Power Control (MAN-PC)* MANET Interference Avoidance (MAN-IA) MANET Interference Cancellation (MAN-IC)* <i>*ITAR-Controlled</i>	
POWER INPUT	USB-PD (9V@3A) or 9-32 VDC	
POWER CONSUMPTION	4-13W @ 2W TX Power (SM5200)	
DIMENSIONS	103 x 68 x 13mm (Radio Only) 178 x 124 x 39mm (Total System)	
WEIGHT	214 grams (Radio Only) 648 grams (Total System)	

\* Preliminary Specifications – Subject To Change



SM5200